



# ULTRA POWER-1000

## High Range Water Reducing Self Compacting Super Plasticizer

Admixtures

Surface Treatments

Protective Coatings

Concrete Repairs

Industrial Flooring

Grouts & Anchors,

Adhesives,

Water Proofing

Sealants

### Description

ULTRA POWER -1000 is third generation super plasticizer which shows high water reduction and excellent fluidity or workability performance. It is aqueous carboxylic acid co polymer type super plasticizer having dynamic properties.

### PRIMARY USE

- Microsilica concrete
- Mass concrete pours
- Ready mixed concrete
- Long distance transport
- Pumped concrete
- Casting in hot climates.

### ADVANTAGES

- Provide self compacting concrete
- To significantly reduce the water Consumption of a concrete mix.
- Improve workability
- Increase early and ultimate strengths without additional cement.
- Particularly suitable for increasing workability of ready-mixed concrete at higher temperature or long distance.
- To reduce concrete permeability, reduce water penetration and enhance durability.
- Reduce thermal peaks
- Reduce shrinkage.

### STANDARD

ASTM C494 as type A, F and G

### TYPICAL DOSAGE

Trail mix should used to maximize the benefits.

The normal dosage range is from 0.50 to 2.0 litres/100 kg of cementitious material.

Dosage rate clearly depends upon mix design and requirements. It is suggested to determine a trial mix before going to concrete.

### PROPERTIES

Appearance: Light brown liquid  
Chloride content: Nil to BS 5075

Air entrainment: Typically less than 2.5% additional air is entrained at normal dosages.

Special Gravity 1.155 @ 20°C±2%

### Packing

Ultra power -1000 is packaged in bulk, 210 Liters, 30 Liter

### INSTRUCTIONS FOR USE

#### Mixing patterns

Initial trials should be done with normal concrete. After initial trials, a minor modification to the overall mixture may be made as needed to optimize performance.

#### Curing

Good curing practice should be maintained especially in the case of an overdose. Water or Ultra Cure 603 spray should be applied.

#### Storage

Ultra Power - 1000 has a minimum shelf life of 1 year while stored at 2° - 50°C.

Freezing point: Approximately -3°C

#### Cautions

##### Health and safety

Ultra Power -1000 is non-hazardous. However, it should not be swallowed or allowed to come into contact With skin and eyes.

Gloves and goggles should be used. Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.

If swallowed seek medical attention immediately - do not induce vomiting.

For further information consult the Material Safety Data Sheet available for this product.

#### Fire

Ultra Power-1000 is water based and non-flammable.

#### Cleaning and Disposal

Cleaning and disposal Spillages of Ultra Power -1000 should be absorbed onto sand, earth or vermiculite and transferred to suitable containers. Remaining material should be rinsed down with large quantities of water.

**WARRANTY:** The Ultra Chemicals, LLC. ("Ultra ") solely and expressly warrants that its products shall be free from defects in materials and workmanship for 12 months from the date of purchase. Unless authorized In writing by an officer of Ultra, no other representations or statements made by Ultra or its representatives, in writing or orally, shall alter this warranty. **ULTRA MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME.** If any Ultra product fails to conform to this warranty, Ultra will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Ultra does not authorize anyone on its behalf to make any written or oral statements which in any way alter Ultra's installation information or instructions in its product literature or on its packaging labels. Any installation of Ultra products which fails to conform to such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Ultra's products for the Buyer's intended purposes.

#### Storage:

Avoid to place direct to sun light and always store in shady areas.

#### ISO Certification:

Our production facility at Pakistan is ISO 9001:2008 ISO 14001:2004 by BUREAU VERITAS and UKAS Management



## ULTRA CHEMICALS, LLC. USA

325 Conway, Hill Road, MO, 63901, USA. Ph: 573-429-1105  
info@ultra-chemicals.com, www.ultra-chemicals.com - www.ultragroup.pk

