



ULTRA TILE BOND

For Interior and Exterior Fixing of Ceramics Marble and Decorative Cladding

Admixtures

Surface Treatments

Protective Coatings

Concrete Repairs

Industrial Flooring

Grouts & Anchors,

Adhesives,

Water Proofing

Sealants

USES

Ultra Tile Bond is a high quality adhesive for the permanent fixing of ceramic tiles. It can also be used for fixing of insulating and acoustic boards based on expanded polystyrene etc.

DESCRIPTION

Ultra Tile Bond Cementitious Based powder is available in Grey color.

Advantages

- Interior or Exterior use.
- Water resistant.
- Precision made.
- Easy to use.
- Economical.
- Compact packing.
- For Walls and Floors.
- High adhesive bond strength.
- Long open time.
- Slip resistant.

APPLICATION INSTRUCTION

SURFACE PREPARATION

All surfaces must be sound and thoroughly clean before Ultra Tile Bond is applied. All traces of grease or oil must be removed with Ultra Chemicals degrease. All loose particles of mortar, old wallpaper; paint etc must be physically removed.

SURFACES

Ultra Tile Bond can be applied directly on concrete, cement, screeds, and cement or lime mortar. Special attention must be given to new construction prior to

Commencing filling tiles should not be placed on concrete or block work until all shrinkage movement has taken place.

Note: Ultra Tile Bond should not be used directly on gypsum or gypsum board substrates. Please contact your local Ultra Chemicals office for advice.

MIXING

4.8 to 5.0 Liters of water are required for each 20 kg bag of Ultra Tile Bond. A slow speed drill fitted with a suitable mixing paddle is recommended. Add powder to water and mix until a uniform, lump-free consistency is achieved.

APPLICATION

Ultra Tile Bond is spread on the substrate to a uniform thickness of 2-3mm. This is then combed horizontally.

Place tiles firmly into adhesive bed ensuring good contact with a twisting motion. Only apply to areas which can be tiled in the adhesive's open wet time (up to 1m² at a time).

JOINTS

It is recommended that when fixing ceramic tiles, a minimum spacing of 2mm be left around each tile.

FINISHING

Remove excess adhesive with a damp cloth before material has set. Joint Grouting with Ultra Tile Grout may be commenced 24 hours after tile as been laid.

CLEANING

Ultra Tile Bond should be removed from tools, equipment and mixers with clean water immediately after use. Cured material can only be removed mechanically.

LIMITATIONS:

Ultra Tile Bond Should not be used when the temperature below 5°C and falling. The product should Not be exposed to moving water during application. If any doubt arises concerning temperature or Substrate conditions, consult Local Ultra Chemicals office.

STANDARD:

BS 5980 Type - 1

Storage:

Avoid to place direct to sun light and always store in shady areas.

ISO Certification:

Our production facility at Pakistan is ISO 9001:2008 ISO 14001:2004 by BUREAU VERITAS and UKAS Management

WARRANTY: The Ultra Chemicals LLC. ("Ultra") solely and expressly warrants that its products shall be free from defects in materials and workmanship for 12 months from the date of purchase. Unless authorized in writing by an officer of Ultra, no other representations or statements made by Ultra or its representatives, in writing or orally, shall alter this warranty. **U L T R A M A K E S N O W A R R A N T I E S, I M P L I E D O R O T H E R W I S E, A S T O T H E M E R C H A N T A B I L I T Y O R F I T N E S S F O R O R D I N A R Y O R P A R T I C U L A R P U R P O S E S O F I T S P R O D U C T S A N D E X C L U D E S T H E S A M E.** If any Ultra product fails to conform to this warranty, Ultra will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Ultra does not authorize anyone on its behalf to make any written or oral statements which in any way alter Ultra's installation information or instructions in its product literature or on its packaging labels. Any installation of Ultra products which fails to conform to such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Ultra's products for the Buyer's intended purpose



ULTRA CHEMICALS, LLC. USA

325 Conway, Hill Road, MO, 63901, USA. Ph: 573-429-1105
info@ultra-chemicals.com, www.ultra-chemicals.com - www.ultragroup.pk

