



ULTRA WALL PUTTY

White cement based wall putty

Admixtures

Surface Treatments

Protective Coatings

Concrete Repairs

Industrial Flooring

Grouts & Anchors,

Adhesives,

Water Proofing

Sealants

Description Ultra Wall Putty is a white cement based fine powder which provides an ideal finishing for concrete/cement plastered walls and ceiling. It provides an ideal base for paints.

Applications:

- New surface requires preparation such as removal of dust dirt and foreign matter. In case of cracks, voids & damages it should be repaired. Surface should be in just-wet condition prior to putty application
- Ensure that surface is plastered or made with cementitious material.
- Ensure that surface is totally clean.
- Ensure that surface is just-wet. Over wetting resulting in accumulation of water on surface should be avoided.
- In case of wall expose more water spraying shall be done to take away heat from surface and then bring wall to just wetted condition.
- Product should be mixed in such quantities that it could be used within 2 hours of its preparation.
- Paint could be done after 3 or more days of putty work but is shall be ensured that putty is completely dry before applying paint.

FEATURES/ BENEFITS

- We do not recommend mixing of pigments/strainer in Ultra Wall Putty.
- Quality of painted surface is directly proportional to

quality of un-painted surface. Ultra Wall Putty renders ideal condition as un-painted surface for paint applications.

- Paint can be applied on Ultra Wall Putty with or without primer. However, use of primer shall give cost advantage in case of expensive paints.
- Lustrous white and smooth surface which can be left unpainted.
- Life of Ultra wall putty is as long as the life of grey cement plaster underneath.
- It prevents growth of algae and fungus on walls.
- Any kind of distemper can be applied on it directly.

Shelf Life: 1 year in original, unopened package.

PACKAGING

ULTRA Walls Putty is available in 10 /kg pack.

Coverage:

Minimum two coats of Ultra Wall Putty. Maximum thickness of 1st coat 1.5 mm & Maximum thickness of 2nd coat is 1.0 mm

Approximate achievable coverage is 14 Sft/Kg. However actual coverage achieve depends on the base surface condition & finished thickness.

Mixing-

Mix Ultra Wall Putty slowly in @ 35-40% water by volume to prepare paste of desired consistency..

Mix vigorously for 5-10 minutes

for making lump free and uniform paste.

Mixing could be done manually or by suitable electric mixer.

WARRANTY: The Ultra Chemicals, LLC. ("Ultra ") solely and expressly warrants that its products shall be free from defects in materials and workmanship for 12 months from the date of purchase. Unless authorized in writing by an officer of Ultra, no other representations or statements made by Ultra or its representatives, in writing or orally, shall alter this warranty. ULTRA MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Ultra product fails to conform to this warranty, Ultra will replace the Product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Ultra does not authorize anyone on its behalf to make any written or oral statements which in any way alter Ultra's installation information or instructions in its product literature or on its packaging labels. Any installation of Ultra products which fails to conform to such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Ultra's products for the Buyer's intended purposes.

Regional Sales Office



ULTRA CHEMICALS, LLC. USA

325 Conway, Hill Road, MO, 63901, USA. Ph: 573-429-1105
info@ultra-chemicals.com, www.ultra-chemicals.com - www.ultragroup.pk

